

FOLLOW THE STEPS BELOW:

1. Carefully unpack the fixture. Lay out all parts on a clear surface.
2. Screw the two Mounting Screws (D) onto the Mounting Bracket (C). Mount the Mounting Bracket (C) to the Outlet box (B) using the two Outlet Box Screws (E). Make sure the threads of the Mounting Screws (D) are facing outside when the Mounting Bracket (C), is attached to the Outlet Box (B).
3. Connect the Ground wire from the fixture to the Ground wire from the Outlet Box (B).
4. Connect the White wire from the fixture to the White wire (Neutral wire) from the Outlet Box (B).
5. Connect the Black wire from the fixture to the Black wire (Live wire) from the Outlet Box (B).
6. Cover the three connections using the three Wire Connectors (F). Wrap the three wire connections with electrical tape for a more secure connection. Position the wires back inside of the Outlet Box (B).
7. Place the fixture base on the wall by aligning the protruding Mounting Screws (D) all the way through the holes on the Wall Plate (A).
8. Tighten the fixture to the wall by screwing the two Decorative Nuts (G) onto the protruding Mounting Screws (D).
9. Caulk around the Wall Plate (A) with silicone weather sealant.

Installation is complete. Turn on the power at the circuit breaker or fuse box. Turn the light switch to activate the fixture.

